

JOB SAFETY ANALYSIS

Safety Information for the University of California, Berkeley

FACILITIES SERVICES

OPERATING A 6-INCH JOINER

TASK	HAZARDS	CONTROLS
1. Start exhaust fan.	Flying sawdust from back draft	Open exhaust vent. Wear safety glasses or face shield.
2. Align materials flat on table and flush against fence.	Pinching fingers or hand	Keep fingers and hands away from pinch points.
3. Run material through joiner.	Lacerations to fingers and hands	Keep fingers and hands away from blade. If the top of the material is below the top of the fence, use push bar.
Required Training: 1. Operation of joiner, including use of push bar	Required Personal Protective Equipment (PPE) 1. Safety glasses 2. Face shield	

Other Information:

Contributors:

Created:

JSA Library Number:

Senior EH&S Technician Jim Ostidick; Lead Carpenter Louis Mandrigues
March 2003
FS-CARP-165

For more information about this JSA, contact the *Office of Environment, Health and Safety* at UC Berkeley, 317 University Hall #1150, Berkeley, CA 94720-1150
(510) 642-3073 ● <http://www.ehs.berkeley.edu>

The development of Job Safety Analyses is a Balanced Scorecard initiative of the AVC-BAS Safety Committee, sponsored by the Associate Vice Chancellor-Business and Administrative Services (AVC-BAS) and the AVC-BAS Leadership Team ● <http://bas.berkeley.edu/balancedscorecard>